

Prince Color[®] Multiputz UP

Special Additive for Working the Acrylic and Silicone Paste-Plasters and without Dispersive Cement-Based Adhesives at Temperatures from +1 °C to +5 °C.

Fields of Application

The Prince Color[®] Multiputz UP additive improves the exhaust of evaporated water, accelerating the process of curing of the silicone and acrylic plasters and the dispersive adhesives at temperatures from +1 °C and high air dew point (up to 99 %). The preparation markedly limits the possibility for a leach of ancillary substances and colorants when paste-plasters are applied under adverse weather conditions. In case of dispersive adhesives it shortens the period of their drying.

BEWARE! The product is not suitable for rich hues mixed into the colourless bases of plasters (base 3). Ingredient is white and slightly lighter material applied (through-colored pasty plaster).

Therefore, the mixed material with an additive process Prince Color[®] Multiputz UP always complete facade area.

Technical Data

Composition	mixture of special additives
pH value	11
Density at +20 °C	3-3.2 g/cm ³
Shade	white
Packaging	paper bag of a volume of 0.5 kg

Dosing

Mix Prince Color[®] Multiputz UP of a volume of 0.5 kg into 25 kg of white or already dyed paste-plaster. Use low-speed agitator (up to 450 rpm) to agitate the mixture for a period of at least 3 minutes to let it mature for 3-5 minutes, then agitate it again shortly. Only then the mixture is ready to be applied.

Working Period

The mixture prepared this way which contains Prince Color[®] Multiputz UP additive must be worked at a temperature from +1 °C to +5 °C within 2 hours at the latest. Longer period for its working is inadmissible. Higher temperatures (above +10 °C) accelerate the mixture's curing and drying. The plaster is resistant to weather conditions after 24 hours (temperature must not drop below +1 °C within this period).

Dilution

Not to be diluted.

Storage

In dry storage, protect from moisture, open packages quickly consumed during min. 6 months from the date of manufacture.

Cleaning of tools

With water immediately after use. After the mixture has dried, tools can be only cleaned mechanically.

Safety Measures

Prince Color[®] Multiputz UP has a mild alkaline character. It irritates skin and may cause serious harm to eyes. On prolonged contact with skin it may develop sensitizing effects. Wear protective clothing, goggles, and rubber gloves. In case of contact with eyes rinse with plenty of clean running water and seek prompt medical attention. In case of skin irritation seek medical assistance and put the contaminated clothing to the reserved place.

BASF Stavební hmoty Česká republika s. r. o.
K Májovu 1244
CZ-537 01 Chrudim
T: +420 469 607 111
F: +420 469 607 112
E-mail: info.cz@basf.com
www.basf-sh.cz

05/2011

