

Prince Color® Multi Top FC

Repair solution.

Extent of use

- For outdoor and indoor application.
- Repair solution with fungicidal and bactericidal substances for the cleaning and pretreatment of surfaces infested with mould, algae and moss

Features

- Highly effective, ready to use.
- Colourless.
- Odourless.
- Solvents-free.
- With fungicidal and bactericidal substances.
- Recoatable with dispersion paints of BASF stavební hmoty Česká republika s.r.o. for indoor and outdoor application.

Technical data

Density/specific weight	approx. 1,0 g/cm ³	
Tint	colourless	
Sheen level/surface	matt	
Working temperature (ambient and substrate temperature)	do not apply under temperature below +5 °C and under direct sun shining	
Application	by brush	
Consumption (per 1 coat)*	removing and cleaning coat: 1 l Prince Color® Multi Top FC per approx. 4 m ² depending on substrate application protective coat – pretreatment: 1 l Prince Color® Multi Top FC per approx. 5 m ² depending on substrate application plochy	
Drying time (20 °C/65 % rel. air humidity)	recoatable: after approx. 24 hours	
Colour tinting	–	
Dilution	Do not dilute	

* Non-binding reference value since surfaces and their consumption rates vary. Carry out a test application to assess the exact spreading rate.

Packaging and storage

- Packaging in plastic pail 10 l with lid.
- Storage in dry, cool insulated warehouse with temperature above +5°C. Seal open containers airtight and use up soon.

Substrate preparation

- Substrate must be dry, solid and sound free of silicone, wax, oils, fats and dust (accord. DIN 18363, especially item 3.1.1.).
- Remove brittle paint and old coatings in poor condition entirely.

Application

Infested surfaces cleaning

Indoor: Brush down infested surfaces with brush and steel scraper – in dry condition.

Outdoor: Apply Prince Color® Multi Top FC on the infested surfaces, allow to work in and clean by means of pressure water jet up to 50 bars (do not use high-pressure water jet for ETICS)

Prevention of clean surfaces – not attacked by mosses etc.: 1 x apply saturated amount of Prince Color® Multi Top FC and allow setting – do not rinse.

Poor substrates reinforcement

Poor and limited bearing substrates should be reinforced after sufficient solution drying time (after 24 hours) with primers Prince Color® Multigrund PGM, PGU (do not use primers with solvents for ETICS, only water diluted primers).

Top coat:

Use tried-and-tested dispersion paints for inside and outside and plaster/render as required.

Note

Do not use as additive for dispersion paint Prince Color® – solution precipitation!

Safety instructions

General instructions: In all cases of doubt, or when symptoms persist, seek medical attention. Observe important of unconscious person (breathing, heart activity, pulse). Do not indicate vomiting. Seek medical help.

Inhalation: Remove immediately to fresh air, keep patient warm and at rest. Seek medical attention. Do not inhale vapour. Entire sufficient ventilation.

Skin contact: Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners. Apply suitable repairation cream after washing.

Eye contact: Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.

Ingestion: If swallowed, rinse mouth with plenty of water (only if the person is conscious) and seek medical advice immediately. Keep the injured person rest. Do not induce vomiting.

When spraying use appropriate respiration protection. Use eye and face protection. Use suitable protective gloves. Use suitable protective cream when using repeatedly.

For detail information see Material Safety Data Sheet.

Information for architects and engineers

Consultations on the building sites, additional information, tests approvals and samples descriptions are available at the local technical offices or directly in company residence.

Disposal information

Product is to be disposed in accordance with particular rules valid in country of use.

Do not allow product to reach ground water, water bodies and sewage systems.

BASF Stavební hmoty Česká republika s.r.o.
K Májovu 1244
CZ-537 01 Chrudim
T: +420 469 607 111
F: +420 469 607 112
E-mail: info.cz@basf.com
www.basf-sh.cz